

(12) 按照专利合作条约所公布的国际申请

(19) 世界知识产权组织
国际局



(43) 国际公布日:
2005年2月24日(24.02.2005)

PCT

(10) 国际公布号:
WO 2005/017069 A1

(51) 国际分类号⁷: C10G 1/10, C08J 11/04, C10G 17/02

(21) 国际申请号: PCT/CN2004/000663

(22) 国际申请日: 2004年6月22日(22.06.2004)

(25) 申请语言: 中文

(26) 公布语言: 中文

(30) 优先权:
03146751.2 2003年6月24日(24.06.2003) CN

(71)(72) 发明人/申请人: 谢福胜(XIE, Fusheng) [CN/CN];
中国山东省淄博市临淄区齐鲁石化生活区遄台北区23
号楼2单元502室, (Shandong 255400 CN).

(74) 代理人: 北京安博达知识产权代理有限公司
(AMBOYNA INTELLECTUAL PROPERTY
AGENT LTD.) 中国北京市海淀区蔚门里小区和景
园A座3-102室, Beijing 100088 (CN).

DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR,
HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN,
MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL,
PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA,
ZM, ZW

(84) 指定国(除另有指明, 要求每一种可提供的地区保护):
ARIPO(BW, GH, GM, KE, LS, MW, MZ, NA, SD,
SL, SZ, TZ, UG, ZM, ZW), 欧亚专利(AM, AZ, BY,
KG, KZ, MD, RU, TJ, TM), 欧洲专利(AT, BE, BG,
CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU,
IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR),
OAPI(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG)

本国际公布:


- 包括国际检索报告。
- 包括经修改的权利要求。

(81) 指定国(除另有指明, 要求每一种可提供的国家保护):
AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW,
BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM,

所引用双字母代码和其它缩写符号, 请参考刊登在每期
PCT公报期刊起始的“代码及缩写符号简要说明”。

(54) Title: A PROCESS AND A DEVICE FOR PRODUCING GASOLINE, KEROSENE AND DIESEL OIL FROM
WASTE PLASTIC, RUBBER AND MACHINE OIL

(54) 发明名称: 用废弃塑料、橡胶、机油生产汽、煤、柴油的方法及装置



(57) Abstract: A process and a device that produce gasoline, kerosene and diesel oil from waste plastic, rubber and machine oil, the device comprises successively cracker, fixed bed, Packed tower, fractionating tower, the top part of the fractionating tower connects with gasoline quencher, and the quencher links condenser, separator of oil and water, filter, and gasoline treating column in series, the latter is connected with filter, finished product tank; the kerosene fraction from the middle part of the fractionating tower and the diesel oil fraction from the lower part enter condenser, separator of oil and water, filter, and treating column in series respectively, the residue from the bottom returns back to the cracker. In this invention, quartz and sand are added during cracking; one step process is used in fixed bed; a chemical agent for removing the odor and changing the color is added during the fractionating. The device in this invention has low cost and reduced volume, which simplifies the process and shortens the production cycle, the oil product obtained has good quality and high yield.

[见续页]

BEST AVAILABLE COPY

WO 2005/017069 A1



(57) 摘要

利用废弃塑料、橡胶、机油生产汽、煤、柴油的工艺及装置，依次包括裂解釜、固定床、填料塔、分馏塔，分馏塔的塔顶连接汽油馏分急冷器，急冷器依次连接冷凝器、油水分离器、过滤器、汽油精制塔，汽油精制塔依次连接过滤器、成品罐；分馏塔的中部煤油馏分、下部柴油馏分分别依次连接冷凝器、油水分离器、过滤器、精制塔。分馏塔塔底的重油组分回到裂解釜。本发明在裂解时加入了石英石和沙粒；固定床采用了一步法；分馏过程中加入了除味、改变颜色的化学药剂。本发明设备投资简单、体积可以缩小，工艺简化，缩短了生产周期，得到的油品质量好，收率高。

BEST AVAILABLE COPY